

# 974 NYMAX

**SERIES** *Nylon Multifilament Yarn Braided Sleeving*



## DESCRIPTION

- Braided nylon multifilament yarn construction
- Tensile strength of 1000 lbs/inch
- Extreme heat and flame resistance
- Soft inner jacket for easy installation
- 50% wear at 250°C
- 25% wear at 350°C

## FEATURES

- Available in standard and custom braided configurations
- Available in multiple braided diameters
- Fully braided construction for maximum strength and flexibility
- Available in standard and custom braided configurations



DIMENSIONS	440 (Standard)	440 (Standard)	440 (Standard)	440 (Standard)
	440 (Standard)	440 (Standard)	440 (Standard)	440 (Standard)
Outer Diameter	1.50" (38.1mm)	1.50" (38.1mm)	1.50" (38.1mm)	1.50" (38.1mm)
Inner Diameter	1.25" (31.8mm)	1.25" (31.8mm)	1.25" (31.8mm)	1.25" (31.8mm)
Wall Thickness	0.125" (3.18mm)	0.125" (3.18mm)	0.125" (3.18mm)	0.125" (3.18mm)
Weight	0.15 lbs/ft (0.045 kg/m)	0.15 lbs/ft (0.045 kg/m)	0.15 lbs/ft (0.045 kg/m)	0.15 lbs/ft (0.045 kg/m)

TESTING	440 (Standard)	440 (Standard)	440 (Standard)	440 (Standard)
	440 (Standard)	440 (Standard)	440 (Standard)	440 (Standard)
Tensile Strength	1000 lbs/inch	1000 lbs/inch	1000 lbs/inch	1000 lbs/inch
Heat Resistance	250°C	250°C	250°C	250°C
Flame Resistance	UL-94V0	UL-94V0	UL-94V0	UL-94V0
Chemical Resistance	Acid, Alkali, Solvent	Acid, Alkali, Solvent	Acid, Alkali, Solvent	Acid, Alkali, Solvent

